

PW41 - Super Ear Protector

Collection: Ear Muffs

Range: PPE

Materials: HIPS (High Impact Polystyrene), Stainless Steel

Product information

Ultra light and compact ear muffFolds to palm size for better carriage and to keep cleanIdeal for all day wear but also for intermittent useAdjustable dual pin system provides multiple positioning for better fitExcellent attenuation rate

AS/NZS 1270 (SLC(80) 31dB - Class 5)
EN 352-1 (SNR 30dB)
ANSI S3.19 (25dB)

Ear Muffs

Portwest hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- CE-CAT III
- Folds to palm size for better carriage and to keep clean
- Adjustable dual pin system provides multiple positioning for better fit
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



	Range
Red	-
Yellow	-

PW41 - Super Ear Protector

Commodity Code: 6506101000

Test House

Michael & Associates, Inc. (Notified Body No.:)
2766 W. College Ave Suite 1
PA 16801, United States
Cert No: Q3931A

BSI Group The Netherlands B.V. (Notified Body No.: 2797)
Say Building, John M. Keynesplein 9, 1066 EP
, Netherlands
Cert No: CE 698123 - I

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PW41RER	Red	48.0	40.0	60.0	0.2400	0.1152	5036108134663	15036108636225

PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002

PW41/PS41		SNR 30.4dB				H: 33.0 M: 27.8 L: 21.3			
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	17.8	18.0	22.3	27.2	37.4	33.9	37.4	38.4
C	Standard Deviation (dB)	3.5	2.6	2.0	3.1	3.3	2.2	3.5	5.1
D	Assumed Protection (dB)	14.3	15.4	19.3	24.1	34.0	31.7	33.9	33.3

ANSI TESTING: Michael & Associates, Inc 246 Woodland Drive, State College, PA 16803

PW41/PS41		NRR (NOISE REDUCTION RATING) = 25dB								
A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	17.6	21.8	30.7	39.7	35.5	37.3	39.1	34.6	35.6
C	Standard Deviation (dB)	3.1	2.6	2.9	3.0	3.1	2.8	2.7	2.7	3.8

PW41RER